

WiFi READY | OPZIONALE



Scheda tecnica

## SPLIT PARETE 1X1 SERIE AMBER



Controllo vocale



Protezione Golden Fin



Timer 24 h



Modalità silenziosa



Autopulente

### MODELLI

		ELS026AMBR32	ELS035AMBR32	ELS052AMBR32	ELS071AMBR32	
INT.		ELS026AMBR32-INT	ELS035AMBR32-INT	ELS052AMBR32-INT	ELS071AMBR32-INT	
EXT.		ELS026AMBR32-EXT	ELS035AMBR32-EXT	ELS052AMBR32-EXT	ELS071AMBR32-EXT	
Alimentazione Elettrica	V,F,HZ	220-240V (1 Fase~ 50Hz)				
<b>RENDIMENTO</b>						
Resa in raffreddamento	Capacità	kW	2,6	3,5	5,3	7,0
		Btu/h	9.000 (3.100-11.600)	12.000 (3.800-14.200)	18.000 (6.200-20.900)	24.000 (7.100-27.120)
	Consumo	W	732 (100~1.240)	1.213 (130~1.580)	1539 (140~2360)	2345 (160~2960)
	SEER / Classe Energetica	-	6,3 / A++	6,1 / A++	7,1 / A++	6,1 / A++
Resa in riscaldamento	Capacità	kW	2,91	3,8	5,57	7,31
		Btu/h	10.000 (2.800-11.500)	13.000 (3.700-14.400)	19.000 (4.700-23.000)	25.000 (5.500-30.000)
	Consumo	W	733 (120~1.200)	1.088 (100~1.680)	1480 (200~2410)	2035 (260~3140)
	*SCOP / Classe Energetica	-	4/A+	4/A+	4/A+	4/A+
<b>CARATTERISTICHE</b>						
Unità interna	Potenza sonora (H)	dB(A)	54	55	55	59
	Pressione sonora (H/M/L)	dB(A)	38,5/32/25/21	40,5/34,5/25/22	42,5/36/26/25	45/40,5/36/28
	Portata aria	m <sup>3</sup> /h	466/360/325	540/430/314	840/680/540	980/817/662
	Gamma di temperatura selezionabile	°C	16~31			
Unità esterna	Potenza sonora	dB(A)	62	65	61	67
	Pressione sonora	dB(A)	55,5	56	56	59
	Portata aria	m <sup>3</sup> /h	1.750	1.800	2.500	3.000
	Temperatura di funzionamento	°C	-15~50   -15~30			
Refrigerante	Tipo / Carica	- / Kg	R32/0,55	R32/0,55	R32/1	R32/1,6
	Carica addizionale >5mt	g/m	12	12	12	24
<b>DIMENSIONI E PESI</b>						
Unità interna	Dimensioni nette (LxA×P)	mm	805×285×194	805×285×194	957×302×213	1.040×327×220
	Dimensioni lorde (LxA×P)	mm	870×365×270	870×365×270	1035×380×295	1120×405×315
	Peso netto / lordo	Kg	7,6/9,7	7,6/9,7	10/13	12,3/15,8
Unità esterna	Dimensioni nette (LxA×P)	mm	720×495×270	720×495×270	800×554×333	845×702×363
	Dimensioni lorde (LxA×P)	mm	835×540×300	835×540×300	920×615×390	965×765×395
	Peso netto / lordo	Kg	23,2/25	23,2/25	32,7/35,4	51/55
<b>CONNESSIONI</b>						
Linee Frigorifere	Liquido - Gas	Pulg.	1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"	3/8" - 5/8"
	Lunghezza max.	m	25	25	30	50
	Dislivello max.	m	10	10	20	25
Connessioni elettriche	Alimentazione	mm	2x2,5 + T			
	Interconnessione	mm	4x2,5 + T			
CODICE EAN	Set		8435483815254	8435483815247	8435483815230	8435483815223
	Modulo WiFi Opzionale		8435483801844	8435483801844	8435483801844	8435483801844